



1. General

		Move-in Standard	Move-out Standard
1. G	eneral		
1.1	Welcome	The welcome pack shall be emailed to each resident upon move-in and will include information on living in Service Family Accommodation, including on: Preventing damp, mould and condensation Making requests (such as running a business from home or keeping a pet) Ordering furniture or having it removed Arranging insurance for your home How to report faults Attached to the welcome pack email (where relevant) will be: Any statutory compliance documentation (such as gas safety record and NICEIC electrical checks) The welcome pack email will also link to important documentation such as the 14 day observation form. Where relevant, physical Instruction manuals relating to components within the property (for example boiler instructions, where relevant) will be left in the property.	Any manuals that were handed over at move- in and any additional guides received during occupancy should remain in the property. At move-out, all belongings (possessions and pets) and rubbish must be removed from the property before the move-out appointment.



1.2 Cleanliness

<u>Flooring</u>

Carpets - Shall be vacuumed, stain free and free from infestation throughout the property

All other flooring - Shall be clean and free of any dirt, stains, rips and scratches

Interior Features

Walls and ceilings - Shall be clean and free from stains, dust, finger marks dents or holes, ceilings to be cleared of cobwebs

Woodwork - Tops of doors, door frames, skirting boards, picture rails, cupboard shelves shall be washed.

Windows - All glass, frames and sills shall be cleaned, free from smears, finger marks and mildew/mould. All visible parts of the frame shall be visibly clean when the window is open.

Curtains - Rails shall be cleaned and curtains hung without excessive creasing Heating - Storage heaters, boilers, fires, radiators are to be clean and dust free. Fire places are to be swept with all ash removed and chimney recently swept (if used)

Lighting - Cobwebs and dust around fittings shall be removed. Bulbs and florescent tubing left in fitting, shades free from dust and hung. Light diffusers and bowls to be clean inside and out and refitted

Vents and extractor fans - Shall be free from dust

Bathroom and WC

Taps - Shall be clean and free from limescale

Plug holes - Shall be clean and free from limescale, debris and hair
Tiles, aqua boards, bath panels - Shall be clean and free from marks, water
splashes and limescales. Gaps between tiles and silicon joinery shall be free
from mildew and mould



Baths - Shall be clean and free from limescale and marks

Shower screen- Shall be clean, without staining and marks and free from limescale

Sinks - Clean and free from limescale inside and include the underside of the sink and plinths

Shower cubicle - Shall be clean, without marks, mildew/mould and limescale.

Shower caddies in and outside of the cubicle are to be removed

Toilets - Shall be cleaned, free from limescale inside and outside of the bowl Toilet seats - Shall be clean and secure without excessive dis-colouration Extractor fans - Clean and free from dust

Kitchen and Utility Areas

Cooker - Shall be free from grease and carbon deposits on the hob, inside the oven and the surrounds of the cooker

Cooker hood - Free from grease around the whole unit and a new filter installed Work surfaces - Free from grease, marks and dirt to all exposed areas (edges and accessible undersides)

Wall surfaces - Shall be free from grease, marks, mildew/mould and splash marks

Sinks and taps - Shall be free from grease and limescale inside and out. No debris left in the plug holes

Cupboards and drawers - Shall be clean and free from dust and food inside and out

Outside

External doors and porches - Shall be clean and free from dirt and marks, brass fittings polished

Windows (External) - All glass, frames and sills shall be cleaned





Paths and driveways - Shall be tidy, weed and moss free and swept
Shed and outbuildings - Shall be free from cobwebs and swept
Bins - Shall be empty and cleaned inside and out (excluding communal bins)





Move-in/out Standard Checklist

2. Flooring

		Move-in Standard	Move-out Standard
2. Flo	ooring		
2.1	Under floor surfaces	Floors shall be structurally sound and level as appropriate for the age of the property and type of construction. Floorboards are not to be split or have any protruding nails. Floor surfaces are to be swept/vacuumed prior to laying carpet or vinyl flooring. Floors shall have minimal squeaks as appropriate for the property age and condition. Underlay specifications can be found in this Schedule, Part 7 Voids - Annex B.	Costs associated with damage caused during occupancy, shall be borne by the Occupant.
2.2	Carpet	Carpet is to be stretched to fit grippers. Minor ripples and frayed edges shall be repaired to pose no trip hazard. Carpets shall be fitted to prevent draughts from entering living areas. The carpet specifications can be found in this Schedule, Part 7 Voids - Annex B. Carpets with significant rips are to be repaired before Move-in and defined as follows: ground floor, stairs and landings- one rip greater then 150mm within each room or area; all other areas - one rip greater then 250mm within each room or area. Rips less then stipulated shall be repaired. Carpets are to be replaced due to significant wear and tear before Move-in and defined as follows: ground floor, stairs and landing - wear and tear greater than 0.3m2 within one room or area; all other areas - wear and tear greater than 0.5m2 within one room or area. If the area is always to be covered by furniture, this may be relaxed.	If the carpet on the ground floor, stairs and landings has one rip greater then 150mm within each room or area; all other areas: one rip greater then 250mm within each room or area, the cost for replacing the carpet shall be borne by the Occupant.





2.3	Vinyl	Vinyl flooring is to be used in all bathrooms, WC, kitchens and utility rooms if floor tiles or hard flooring are not already installed and to Move-in Standard set below. Vinyl flooring is to be sealed at the perimeter with silicone sealant including around sanitary fittings. The vinyl specifications can be found in this Schedule, Part 7 Voids - Annex B. Patch repairs are to be made on rips sized 150mm or less using matching material and colour to the existing flooring. Floor surfaces are to be replaced if more than 150mm in size or there is more than one rip of any size within the same surface area. Worn areas over 0.3m2 shall be replaced.	Cost associated with rips caused during occupancy that are greater than 150mm and requires replacement, shall be borne by the Occupant.
2.4	Tiling	Tiling shall be grouted and sealed at all edges and around sanitary fittings. Tiles shall not be cracked or loose. If there are no sharp edges, small chips less than 10mm across are acceptable. Where a replacement tile is required, it shall match existing colour, size, style as close as possible using commercially available materials or replaced entirely with vinyl.	Costs associated with damage caused during occupancy, shall be borne by the Occupant.
2.5	Wooden and laminate flooring	Wood and/or laminate flooring shall be flat without cracks and nails protruding though. Where areas need to be replaced, it shall match existing flooring.	Wood and laminate flooring should be free from burn marks, water marks, paint marks, excessive scratches or individual scratches of more than 150mm. No part of the flooring should be missing. Costs associated with damage caused during occupancy, shall be borne by the Occupant.
2.6	Naploc fittings	Appropriate 'Naploc' aluminium strips to be fitted to flooring at all internal doors. Flooring must be secured down with the Naploc so as not to pose a trip hazard.	Costs associated with damage caused during occupancy, shall be borne by the Occupant.





Move-in/out Standard

3. Interior Features

		Move-in Standard	Move-out Standard
3. Int	terior featur	es	
3.1	Ceilings	Plasterboard wall and ceiling joints shall be secure and joining tape to be intact. Ceiling finishes (other than those with a textured coating) are to be smooth, level and without any cracking. Ceiling surfaces can have minor blemishes, bumps, dents and marks or evidence of previous repairs appropriate to the age and condition of the property. Polystyrene tiles and coving are to be removed and replaced with plasterboards or plastered to create a smooth and level surface without cracks.	Damages to ceilings made during occupancy, must be filled, smoothed down and painted white. If damage is caused during occupancy and not repaired by Move-out or repairs can be viewed in daylight from a distance of 3 metres, the cost of repair shall be borne by the Occupant.
3.2	Wall surfaces	Wall surfaces must be appropriate to the area that it is located in the house (kitchens and bathrooms). Surfaces may have minor blemishes, bumps, dents and marks and evidence of previous repairs appropriate to the age and construction of the property. All un-bonded or water damaged plaster or plaster displaying evidence of physical movement shall be repaired and redecorated. All nails, screws and picture hooks are to be removed and filled before decoration.	Costs associated with damage caused during occupancy, shall be borne by the Occupant. The occupant may leave up to 4 picture hooks per room without charge
3.3	Staircase	Staircases shall be secure, structurally sound with handrails at least on one side of the staircase for the full length of the staircase.	Costs associated with damage caused during occupancy, shall be borne by the Occupant.



3.4	External	Doors shall be draught proof and watertight under normal weather conditions.	All keys received at Move-in shall be returned
	doors	Doors shall lock securely. Replacement doors shall conform with current	at Move-out. If damage is caused during
		Building Regulations and British Standards. Where only a cylinder lock is fitted	Occupancy, the cost of repair shall be borne
		this shall have a deadlock facility. Hinges, latches, stays, restrictors and locks	by the Occupant. If a cat flap is installed
		shall be functional, fit-for-purpose and complete. Letter plates shall be	during occupancy, it shall be removed before
		draught proof and watertight. Individual fitting replacement is acceptable and	Move-out with the door panel made good
		shall match existing colours and style as closely as possible using widely	unless there has been written approval for it to
		available commercially available materials. Locks shall have at least 2 keys	remain. If cat flap is left in the door at Move-
		and front doors shall be fitted with a security chain / restraint. Fobs for	out and there has not been written approval to
		communal flats shall be supplied if necessary, for ingress. Cat flaps shall be	leave, all costs associated with repair shall be
		removed. and the door panel made good; if appropriate the door panel or door	borne by the Occupant.
		shall be replaced.	
3.5	Internal	All doors shall be sound (not de-laminated), free opening and not foul on the	If damage is caused during occupancy and
	doors	door frame, or carpet/floor finishes to cause damage to paint or surface finish.	not repaired by Move-out or repairs can be
		Non-essential screws and nails shall be removed and any holes, dents, and	viewed in daylight from a distance of 2 metres,
		scrapes in doors are to be filled before decorating. Doors shall latch fully and	the cost of repair shall be borne by the
		remain closed. Where required to meet current Building Regulations and Fire	previous Occupant.
		Risk Assessment recommendations, Fire doors shall meet current Building	
		Regulations and British Standards. Where installed over and above current	

Regulations, existing fire doors are not required to be replaced if they meet the contracted condition standard. Locks, latches, catches, bolts, handles, knobs

springs to return the handle but not necessarily to an exact horizontal position.

etc. are to function correctly, and where appropriate are to have internal

It is not necessary to provide missing keys providing the door is unlocked.

Bathroom and toilet doors shall be lockable. Doorstops shall be fitted where there is a possibility of damage being caused by door handles, coat hooks etc.

Glass inlays and wall features below 1500mm shall be kitemarked or





		laminated with safety films. Doors that require replacement, are to be replaced as per Building Regulations.	
3.6	Water pipes	There shall be no visible leaks from water pipes, taps, stopcocks or waste fittings. Wastes are to be clear from debris and drain freely. All pipework should be adequately fitted. Exposed visible metal pipe work shall be painted, except in airing cupboards, storage areas etc. Horizontal surfaces shall be dust free.	Costs associated with damage caused during occupancy, shall be borne by the Occupant.
3.5	Misc.	All existing skirting, architraves, facings, radiators etc. shall be complete and properly fixed.	If damage is caused during occupancy and not repaired by Move-out or repairs can be viewed in daylight from a distance of 2 meters, the cost of repair shall be borne by the Occupant.



Move-in/out Standard

4. Decoration

		Move-in Standard	Move-out Standard
4. De	ecoration		
4.1	Ceilings	Ceilings are to be painted white and free from bubbling, cracking, staining, mould and mark when viewed in daylight from a distance of 3 metres.	Damages to ceilings made during occupancy, must be filled, smoothed down and painted white. If damage is caused during occupancy and not repaired by Move-out or repairs can be viewed in daylight from a distance of 3 metres, the cost of repair shall be borne by the previous Occupant.
4.2	Painted surfaces	Walls are to be painted silk magnolia or silk white and free of bubbles, cracks, stains, drips, mould and marks when viewed in daylight from a distance of 2 metres. Wood surfaces where decorated are to be painted (gloss white), stained or varnished as appropriate. Only walls that have been previously decorated with painted plaster, ceramic tiling, wallpaper or painted wood chip paper are to be maintained and decorated. Feature brickwork does not require to be decorated. Radiator rollers are to be used to paint the walls behind radiators, it is not required for the radiators to be removed or loosened.	Damages to walls (including removal of more than 4 picture hooks) made during occupancy must be filled, smoothed down and painted with silk magnolia or silk white paint. All walls within the room must be the same colour. If damage is caused during occupancy and not repaired by Move-out or repairs can be viewed in daylight from a distance of 2 metres, the cost of repair shall be borne by the previous Occupant.
4.3	Wallpaper surfaces	Rips and tears in wallpaper covering a single wall, are to be repaired if less than 150mm2. If damage is more than 150mm2, the wall covering shall be replaced and match the remaining walls. Depending on the age of a property and the condition of the wall surfaces, the use of painted wood chip wallpaper	If damage is caused during occupancy and not repaired by Move-out or repairs can be viewed





		is acceptable. Where there is not an entitlement to wallpaper and where replacement is required, consideration shall be given to replacing with painted plaster to take note of the frequency of change of Occupant.	in daylight from a distance of 2 metres, the cost of repair shall be borne by the Occupant.
4.4	Internal doors	Where painted, doors shall be white gloss, same door finishes throughout the property are desirable. Unpainted doors if required, shall be treated with the appropriate products.	If damage is caused during occupancy and not repaired by Move-out or repairs can be viewed in daylight from a distance of 2 metres, the cost of repair shall be borne by the Occupant.
4.5	Tiled surfaces	Wall tiles must be appropriate for use. Tiling shall be grouted and sealed at all work surfaces. Tiles shall not be cracked or loose, but small chips less than 10mm across are acceptable, if there are no sharp edges. Where replacement is required tiles shall match existing colour, size, style as closely as possible using commercially available materials. Where more than 25% of tiles are to be replaced, all tiles shall be changed. Where complete re-tiling is required, tiles shall be white and square with white grouting. Any joint that is excessively discoloured or incomplete or likely to leak, is to be replaced.	If damage is caused during occupancy and not repaired by Move-out or repairs can be viewed in daylight from a distance of 2 metres, the cost of repair shall be borne by the Occupant.
4.6	Misc.	All existing skirting, architraves, facings, radiators etc. shall be painted gloss white.	If damage is caused during occupancy and not repaired by Move-out or repairs can be viewed in daylight from a distance of 2 metres, the cost of repair shall be borne by the Occupant.





5. Bathrooms, WC and Cloakrooms

		Move-in Standard	Move-out Standard
5. Ba	athrooms, W	C and Cloakrooms	
5.1	Toilets	Toilets shall be fully functioning with no cracks or chips that are likely to have a detrimental effect on the structural integrity of the fitting. Contact surfaces shall have a smooth surface and be free from dents and chips.	Costs associated with damage caused during occupancy, shall be borne by the Occupant.
5.2	Toilet seats	Toilet seats shall be secure with properly operating hinges and a lid. Lid shall be free from stains; cracks and chips, sit secure and level on the WC pan. Wooden toilet seats are to be accepted provided they are in good condition.	Refer to Cleanliness at 1.2
5.3	Bathroom suite	Individual bathroom fittings may be replaced without replacing the complete bathroom suite. Any replacement features shall meet the specification laid out in RAMS Schedule 28, Part 10 Archetype Works - Annex B. Taps shall be functional, secure, have indicators denoting which is hot and cold, and not drip. Hand basins and baths shall have plugs and chains (unless fitted with a pop-up plug and lever mechanism). All are to be in good working operation. Wall tiles and aqua boards must be appropriate for use (e.g., where a shower is fitted). All toilets shall have a toilet roll holder in close proximity.	Costs associated with damage caused during occupancy, shall be borne by the Occupant.





5.4	Baths	Minor chips and blemishes are acceptable in baths with enamelled surfaces	Costs associated with damage caused during
		where the chips are less that 10mm across, provided they do not leave sharp	occupancy, shall be borne by the Occupant.
		edges and are not in a contact area. It is acceptable for repairs to be carried	
		out to chips in enamelled baths as long as a reasonable attempt has been	
		made to match colours. Any replacement baths shall meet the specification	
		laid out in RAMS Schedule 28, Part 10 Archetype Works - Annex B. Baths must	
		have bath panels fitted where appropriate. The bath shall have a plug and	
		chain (unless fitted with a pop-up plug).	
5.5	Shower	Replacement showers shall be fitted appropriately to the space available. Any	Costs associated with damage caused during
		replacement baths shall meet the specification laid out in RAMS Schedule 28,	occupancy, shall be borne by the Occupant.
		Part 10 Archetype Works - Annex B.	
5.6	Shower	Shower curtain rails must be positioned so that the curtain hangs inside the	Refer to Cleanliness at 1.2 for shower screen.
	curtain	bath when in use. A new shower curtain shall be provided and hung on each	
		change of Occupancy.	
5.7	Towel rails	Where fitted, towel rails, radiators and extractor fans to be in working order.	Costs associated with damage caused during
			occupancy, shall be borne by the Occupant.
5.8	Joinery	The junction of a sanitary fitting and wall or floor surface is to have a suitable	Refer to Cleanliness at 1.2
		plastic fitting or silicone sealant joint. Joints shall be free from mould and	
		limescale. Any joint that is excessively discoloured or incomplete or likely to	
		leak is to be replaced. Any repairs or replacements shall match existing colour	
		as closely as possible using widely commercially available materials, with	
		sealant finished in a similar profile.	





6. Kitchens

		Move-in Standard	Move-out Standard
6. Ki	tchens		
6.1	Cupboard doors	Wall cabinets and floor units must be securely fixed to the wall. Cabinet doors and drawers shall be securely fitted to the carcass and should allow unrestricted use. Where adjustable, doors shall align with each other and with carcases (adjust and reposition hinges / door to a maximum misalignment of 8mm). Individual door replacement is acceptable and shall match existing colour, size, style as closely as possible using commercially available materials. All doors shall open, close and have an appropriate means of operating. Hinges shall be functional and have all fixings.	Refer to Cleanliness at 1.2 Costs associated with damage caused during occupancy, shall be borne by the Occupant.
6.2	Work surfaces	Work surfaces must be fit for preparing food and easily cleaned. Surfaces shall be free from chips, burns and cracks. If a suitable repair cannot be completed, individual worktop replacement is acceptable and shall match existing colour, size, style as closely as possible using commercially available materials. Moisture contamination (blown) worktops and carcases where a suitable repair cannot be completed shall be replaced.	Refer to Cleanliness at 1.2 Costs associated with damage caused during occupancy, shall be borne by the Occupant.
6.3	Extractor fan	Fans, vents and grills where fitted, shall be in working order. New filters for extractor hoods are to be fitted.	Refer to Cleanliness at 1.2 Costs associated with damage caused during occupancy, shall be borne by the Occupant.





6.4	Cookers	A cooker (gas or electric) is to be provided, be in full working order and be complete with grill pan, handles, oven shelves, knobs and pan supports. Cooker restraints shall be fitted to all freestanding gas cookers. Any replacement cookers and/or hobs shall meet the specification laid out in RAMS Schedule 28, Part 10 Archetype Works - Annex A.	Refer to Cleanliness at 1.2 Costs associated with damage caused during occupancy, shall be borne by the Occupant.
6.5	Sinks	Sinks and draining boards are to be fit for purpose and without significant dents or scratches. Sink units are to be sealed at work surfaces and all edges. Taps shall be functional, secure, have indicators showing which is hot and cold and not drip. Sinks shall have plugs and chains attached (unless fitted with a pop-up plug and lever mechanism).	Refer to Cleanliness at 1.2 Costs associated with damage caused during occupancy, shall be borne by the Occupant.





Move-in/out Standard

7. Windows

		Move-in Standard	Move-out Standard
7. Wir	ndows		
7.1	Window seals	All windows that open shall be fully operational. Windows shall be draught free and watertight under normal weather conditions. Window frames shall be sealed to prevent water ingress. Hinges, latches, stays, restrictors, and locks shall be functional, fit-for-purpose and complete. Double glazed windows are to be free from moisture between the glazing. Where practical, window keys shall be replaced. If the window lock has to be replaced in order to provide missing keys, providing the window is unlocked it is not necessary to replace the lock. Trickle vents, where fitted, shall work effectively and be draft free when closed.	Refer to Cleanliness at 1.2 Key for windows received at Move-in shall be returned at Move-out Costs associated with damage caused during occupancy, shall be borne by the Occupant.
7.2	Window restrictors	Opening windows apart from those on the ground floor shall be fitted with restrictors.	Costs associated with damage caused during occupancy, shall be borne by the Occupant.
7.3	Curtain track, curtain blinds and fittings	All windows shall have curtain rails and rings/hooks, unless it is a bathroom, WC, kitchen or utility window that has been fitted with a blind. Where curtain tracks are provided, they shall be securely fixed and have sufficient curtain rings or hooks. Curtains that have been provided are to be clean, ironed and hung appropriately. Curtains, blinds and other window coverings shall be fit for purpose and in good condition. Minor damage to curtains shall be repaired.	Curtains that have been provided shall be left in the property hung. If curtains have been stored during occupancy, the curtains are to be pressed before being hung and without excessive creases. Costs associated with damage caused during occupancy, shall be borne by the Occupant.





8. Gas and Electrical Installation and Application

		Move-in Standard	Move-out Standard
8. Ga	s and Electric	al Installation and Applications	
8.1	Utility meters	Card or token utility meters are to be replaced with a non-card or token utility meter.	None
8.2	Electrical installation	The electrical installation is to be in working order. Consumer units and fuse panels are to be labelled. Installed earth bonding is to be secure.	None
8.3	Electrical fittings	All switches, sockets etc. shall be securely fixed. All switches, sockets etc. with visible signs of overheating, cracking, or damage shall be replaced. Bare cables or exposed insulation is to be rectified. Metal switches shall be earthed or replaced.	None
8.4	Kitchen switches	Cooker and other kitchen switches shall be labelled, unless their purpose is unambiguous.	None
8.5	Light fittings	Light fittings are to be in working order with a bulb or tube fitted. Light fittings within a room shall match. Ceiling roses, pendants and cord shall not expose any wiring or terminations. Pull cords replaced where not functioning.	Bulbs and tube fittings to remain in the property and be working. Costs associated with damage caused during occupancy, shall be borne by the Occupant.
8.6	Shades and diffusers	Lampshades or light bowls shall be provided. Where glass shades are fitted, the ceiling and wall lights shall match like for like. Fluorescent light fittings are to have a suitable diffuser fitted.	Shades and light fittings to remain in the property. If they were stored while Occupied, they are to be put back on the light fitting before Move-out. Costs





			associated with damage caused during occupancy, shall be borne by the Occupant.
8.7	Smoke alarm	A smoke alarm in working order shall be fitted on each floor, with additional alarms where layout or size of property dictates.	None
8.8	CO detector	A CO detector in working order shall be fitted in each property with an open flue gas or oil appliance, with additional detectors where layout or size of property or installed gas appliances dictates.	None
8.9	Electrical cables	Any electrical cabling including telephone and intruder alarm cabling shall be functional and securely clipped to walls.	None





Move-in/out Standard

9. Heating

		Move-in Standard	Move-out Standard
9. He	ating		
9.1	System	The heating system is to be in working order, with the appropriate test certificates. Boilers, header tanks, radiators, hot water storage cylinders, heating pumps, isolation valves, radiator valves and electric heaters shall be securely fixed, show no external sign of significant corrosion and wet systems shall have no visible leaks or discharges from overflow pipes. Hot water cylinders shall be insulated.	None
9.2	Boiler	Boiler enclosure is to be intact. Replacement boilers shall be compliant with all statutory and mandatory regulations. Any replacement boilers shall meet the specification laid out in RAMS Schedule 28, Part 10 Archetype Works - Annex C.	None
9.3	Radiators	Any thermostatic radiator valves (TRVs) are to be functional and free from dirt and dust. A suitable dust cap is to be fitted to the lock shield valve. Radiator drain valves are to be in working order and the radiators balanced and bled.	None
9.5	Feature fire	Where provided, the focal feature fire (gas or electric) is to be in a safe, clean and working order. Where replacement of gas fires is required, consideration shall be given replacing with alternative requiring less maintenance and testing (including electrical fires).	Costs associated with damage caused during occupancy, shall be borne by the Occupant.





9.6	Open	Open fires shall be safe, clean and in working order. Chimneys shall be swept	Refer to Cleanliness at 1.2
	fireplaces	and in working order.	
	and		
	chimneys		





Move-in/out Standard

10. External Areas

		Move-in Standard	Move-out Standard
10. Ex	ternal Areas		
10.1	Visual roof inspection	The roof shall undergo a visual inspection of the roof to ensure it is sound and water does not penetrate. The guttering, gullies and downpipes are to be serviceable and free from debris and weeds.	None
10.2	TV aerial	Where fitted, TV aerials and cabling shall be functional, in working order and securely clipped to walls.	None
10.3	External decorated surface	The condition of the external decoration surfaces and any additional necessary works shall be recorded in the Housing Specific Task Schedule (HSTS).	None
10.4	External walls	External property walls are to be structurally sound. Unless structurally significant, or shall cause weather damage to the property, cracks greater then 10mm in brick or block work are to be repaired. Non-urgent structural repairs shall be recorded in the HSTS.	None
10.5	Hard surfaces	Hard surfaces (paths, car parking areas, patios, etc) within the property boundary shall be swept, weed and moss free. Hard surfaces shall be free of significant standing water and be free of trip hazards. Steps with an adjacent fall of greater than 600mm shall have handrails.	Refer to Cleanliness at 1.2 Costs associated with damage caused during occupancy, shall be borne by the Occupant.
10.6	Hand rails	Handrails shall be securely fixed and be of sufficient strength to provide restraint.	None





10.7	Fences and	Fences shall be secure and fit for purpose to prevent egress by minors and	Costs associated with damage caused
	gates	canines. Gaps larger then 150mm are to be filled. Gates to be fitted with	during occupancy, shall be borne by the
		operational bolts and latches and be able to close securely.	Occupant.
10.8	Trees	All self-set trees (up to 75mm diameter) shall be removed. All trees inappropriate for their location or those adjacent to footpaths, highways and structures (e.g. buildings, lighting columns, signs and fences) shall be removed. Trees overhanging or encroaching security fence lines, boundary walls, fences, utility services, street furniture are to be pruned back to a minimum of 1m clearance and maintained as such. Formative pruning shall remove epicormic growths and root suckers.	None
10.9	Climbing plants	All ivy and climbing plants shall be removed (severed and poisoned, stripped and dug out at base).	None
10.10	Hedges and shrubs	Borders and flowerbeds are to be tidy, weeded and cultivated. Hedges and shrubs are to be maintained to a manageable 1.8m height and 1m width. All dead, controlled and dangerous species are to be removed.	Hedges and shrubs below 1.8m in height and 1m in width at Move-in, shall be maintained by the Occupant. If hedges and shrubs exceed 1.8m on Move-out, the cost of ground maintenance shall be borne by the Occupant.
10.11	Ground clearance	Gardens are to be free of all litter, excrement and garden waste. Fallen leaves, debris and windfall fruit shall be removed 2 days prior to the Move-in, with new leaves, debris and windfall fruit occurring during the two days allowed to remain.	During occupancy, gardens shall be maintained to a tidy condition including cutting the grass, maintaining the hedges flowerbeds and existing shrubs, collection of leaves and fallen fruit, and the disposal o garden refuse.





10.12	Green	The garden shall be in the majority, an even surface. All individual areas of	Refer to Cleanliness at 1.2. The garden
	space	wear greater than 5% of the grassed area are to be reinstated by seeding with seed comparable to the current grass type. Unless wet or frost conditions prevent cutting, the grass shall be between 25mm to 40mm. Grassed areas that abut hard surfaces are to be trimmed using a strimmer. Scalping of lawn edges shall be completed. All arisings from grass cutting to be removed. Awnings, sandpits, swings, and other temporary structures shall be removed.	should be maintained to a tidy condition and any temporary structures removed.
10.1	Out- buildings	Communal areas are to be clean, serviceable and free from rubbish. All outbuildings including sheds, stores, etc shall be sound and fit for purpose. Where a lock is provided, 2 keys shall be provided.	Refer to Cleanliness at 1.2
10.14	Misc.	A clothes line or rotary dryer shall be provided. Where replacement is necessary, ten linear metres minimum of drying space over 1.5m high shall be provided where practical. All necessary refuse and recycling bins shall be present, serviceable, empty and clean.	Refer to Cleanliness at 1.2





11. Garage

		Move-in Standard	Move-out Standard
11. G	arage		
11.1	Structural integrity	Garage roofs shall be sound and prevent the ingress of water under normal weather conditions. Walls shall be sound and fit for purpose.	Costs associated with damage caused during occupancy, shall be borne by the Occupant.
11.2	Doors	Doors shall be secure, open and close with ease and shall be capable of being locked. Where a lock is provided, 2 garage keys shall be provided.	Costs associated with damage caused during occupancy, shall be borne by the Occupant.
11.3	Drainage	Under normal weather conditions there shall be no standing water within the garage.	Costs associated with damage caused during occupancy, shall be borne by the Occupant.
11.4	Electrical	Lighting and power where provided shall be safe and operational.	Costs associated with damage caused during occupancy, shall be borne by the Occupant.





15. Defence Accommodation Stores (DAS)

		Move-in Standard	Move-out Standard
15. D	efence Acc	ommodation Stores (DAS) - Responsibility by the NAMS supplier	
15.1	Furniture	All furniture is to be serviceable, fit for purpose and erected in the room it is intended for.	Costs associated with damage caused during occupancy, shall be borne by the Occupant.